



Intruder® ANSI • CE • CSA •



Integrated nosepiece // Lightweight frameless protection
// Foam padding is available in select options // Custom imprinting available

Lens and Temples | 13 Variations

- S4110S ●●● Clear
- S4110ST ●●● Clear AF
- S4110STM ●●● Clear **H2MAX AF**
- S4110SUC ● Uncoated Clear
- S4120S ●●● Gray
- S4120ST ●●● Gray AF
- S4120STM ●●● Gray **H2MAX AF**
- S4130S ●●● Amber
- S4160S ●● Infinity Blue
- S4170S ●● Silver Mirror
- S4175S ● Blue Mirror
- S4180S ●● I/O Mirror
- S4180ST ● I/O Mirror AF

Foam Padded Frame | 3 Variations

- S4110STFP ● Clear AF
- S4120STFP ● Gray AF
- S4180STFP ● I/O Mirror AF

Black Temples | 1 Variation

- SB4110S ●● Clear

Blue Temples | 1 Variation

- SN4110S ●● Clear

Red Temples | 1 Variation

- SR4110S ●● Clear



SB41



SN41



SR41

Mini Intruder ANSI •

Mini Intruder has all the great features of Intruder in a design better suited for smaller facial sizes

Lens and Temples | 5 Variations

- S4110SN ● Clear
- S4110SNT ● Clear AF
- S4120SN ● Gray
- S4130SN ● Amber



119 mm



129 mm

i Mini Intruder is about 8% smaller than the Intruder.

Intruder and Mini Intruder Multi-Colors

ANSI • CE • CSA •

Sold in dozen quantity only // Comes with six assorted temple colors: red, blue, green, purple, orange and black // Multi-pack includes two of each temple color with clear lenses // Perfect for work areas where color coding is necessary // Custom imprinting available

Multi-Color Temples | 2 Variations

- S4110SMP ●●● Clear (Intruder)
- S4110SNMP ● Clear (Mini Intruder)



P 800.736.8673 // F 901.861.4967 // W PYRAMEXSAFETY.COM

DISTRIBUIDOR AUTORIZADO:



LA PAZ
Av. Montes Nº 611 casi Esq. Uruguay.
Telf. 2285854 - 2265837
Email: hergo@hergo.com.bo

SANTA CRUZ
Av. Alemana Esq. Calle Majo Nº 2335
casi 3er anillo.
Telf. 3442820
Email: hergoscruz@hergo.com.bo

POTOSÍ
Av. Highland Players Nº 265
Telf. 6248020
Email: admptosi@hergo.com.bo

Intruder®

General Specifications

Weight: 23.1 gm
 PD: 64 mm
 Bridge: 17.27 mm
 Lens base: 10 curve
 Lens size diagonal: 77.08 mm
 Lens size vertical: 43.38 mm
 Lens thickness: 2.5 mm
 Overall length (lens - tip): 156 mm
 Overall width (hinge - hinge): 135.5 mm
 Closest point between temples: 91.53 mm
 Closest point between lens: 16.67 mm

Materials

Lens: polycarbonate
 Temples: polycarbonate
 Hinge: polycarbonate
 Screw: stainless steel

Part No.	Lens Markings	Frame Markings
S4110S	P Z87 + U6	P Z87 + / P c SEI Z94.3
S4110ST	P Z87 + U6	P Z87 + / P c SEI Z94.3
S4110STM	P Z87 + U6 X	P Z87 + / P c SEI Z94.3
S4110SUC	P Z87 + U6	P Z87 +
S4120S	P Z87 + U6 L3	P Z87 + / P c SEI Z94.3
S4120ST	P Z87 + U6 L3	P Z87 + / P c SEI Z94.3
S4120STM	P Z87 + U6 L3 X	P Z87 + / P c SEI Z94.3
S4130S	P Z87 + S	P Z87 + / P c SEI Z94.3
S4160S	P Z87 + S	P Z87 + / P c SEI Z94.3
S4170S	P Z87 + S	P Z87 + / P c SEI Z94.3
S4175S	P Z87 + S	P Z87 +
S4180S	P Z87 + U6 L1.7	P Z87 + / P c SEI Z94.3
S4180ST	P Z87 + U6 L1.7	P Z87 +
S4110STFP	P Z87 + U6	P Z87 +
S4120STFP	P Z87 + U6 L3	P Z87 +
S4180STFP	P Z87 + U6 L1.7	P Z87 +
SB4110S	P Z87 + U6	P Z87 + / P c SEI Z94.3
SN4110S	P Z87 + U6	P Z87 + / P c SEI Z94.3
SR4110S	P Z87 + U6	P Z87 + / P c SEI Z94.3
S4110SMP	P Z87 + U6	P Z87 + / P c SEI Z94.3

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 S: Special Purpose
 X: Tested Anti-fog
 UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV
 Visible Light Filters
 L1.7: 55% Max. Visible Light
 L3: 18% max visible light

Temple Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices

Mini Intruder®

General Specifications

Weight: 17.9 gm
 PD: 62 mm
 Bridge: 14.17 mm
 Lens base: 11 curve
 Lens size diagonal: 69.43 mm
 Lens size vertical: 39.92 mm
 Lens thickness: 2.1 mm
 Overall length (lens - tip): 144 mm
 Overall width (hinge - hinge): 121.8 mm
 Closest point between temples: 77.83 mm
 Closest point between lens: 14.38 mm

Materials

Lens: polycarbonate
 Temples: polycarbonate
 Hinge: polycarbonate
 Screw: stainless steel

Part No.	Lens Markings	Frame Markings
S4110SN	P Z87 + H U6	P Z87 +
S4110SNT	P Z87 + H U6	P Z87 +
S4120SN	P Z87 + H U6 L3	P Z87 +
S4130SN	P Z87 + H S	P Z87 +
S4110SNMP	P Z87 + H U6	P Z87 +

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 H: Small head size
 UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV
 Visible Light Filters
 L1.7: 55% max visible light
 L3: 18% max visible light

Temple Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices

P 800.736.8673 // F 901.861.4967 // W PYRAMEXSAFETY.COM

DISTRIBUIDOR AUTORIZADO:



LA PAZ
 Av. Montes Nº 611 casi Esq. Uruguay.
 Telf. 2285854 - 2285837
 Email: hergo@hergo.com.bo

SANTA CRUZ
 Av. Alemana Esq. Calle Majo Nº 2335
 casi 3er anillo.
 Telf. 3442820
 Email: hergoscruz@hergo.com.bo

POTOSÍ
 Av. Highland Players Nº 265
 Telf. 6248020
 Email: admptosi@hergo.com.bo

Intruder® Readers

General Specifications

Weight: 23.1 gm
 PD: 64 mm
 Bridge: 17.27 mm
 Lens base: 10 curve
 Lens size diagonal: 77.08 mm
 Lens size vertical: 43.38 mm
 Lens thickness: 2.5 mm
 Overall length (lens - tip): 156 mm
 Overall width (hinge - hinge): 135.5 mm
 Closest point between temples: 91.53 mm
 Closest point between lens: 16.67 mm

Materials

Lens: polycarbonate
 Temples: polycarbonate
 Hinge: polycarbonate
 Screw: stainless steel

Part No.	Lens Markings	Frame Markings	
S4110R15	P Z87 + U6	+1.5	P Z87 +
S4110R20	P Z87 + U6	+2.0	P Z87 +
S4110R25	P Z87 + U6	+2.5	P Z87 +

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV

Temple Marking Symbols

+1.50: magnification of +1.5
 +2.00: magnification of +2.0
 +2.50: magnification of +2.5
 P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact

P 800.736.8673 // F 901.861.4967 // W PYRAMEXSAFETY.COM

DISTRIBUIDOR AUTORIZADO:



LA PAZ
 Av. Montes Nº 611 casi Esq. Uruguay.
 Telf. 2285854 - 2285837
 Email: hergo@hergo.com.bo

SANTA CRUZ
 Av. Alemana Esq. Calle Maja Nº 2335
 casi 3er anillo.
 Telf. 3442820
 Email: hergoscruz@hergo.com.bo

POTOSÍ
 Av. Highland Players Nº 265
 Telf. 6248020
 Email: admptosi@hergo.com.bo